

LINERTEC

A-100 Series Automatic Level

A-128 / A-132

- Reliable automatic compensator with the V-shaped suspension tape and air damper
- An easy-to-read horizontal circle
- Minimum focus distance of 0.6m
- Rugged construction usable even in a light rain
- Compact, light weight instrument (1.4 kg.)
- Quick-acting levelling screws for faster setups
- Attainable accuracy of +/- 2.0mm in 1km double run leveling



**Increase your
work efficiency**

Model		A-128	A-132
Telescope	Image		Erect
	Magnification	28X	32X
	Effective aperture		36mm
	Minimum focus distance		0.6m
	Stadia ratio		1 : 100
	Stadia constant		0
Automatic compensator	Working range		±15'
	Setting accuracy		0.5"
	Standard deviation (1Km double run leveling)		±2.0mm
Sensitivity of vials	Circular level sensitivity		10'/2mm
Horizontal circle	Graduation		360° or 400g
	Minimum division		1° or 1g
Dimensions	Instrument	230 (L) x 138 (W) x 140 (H) mm	
	Carrying case	280 (L) x 185 (W) x 185 (H) mm	
Weight	Instrument	1.4 kgs.	
	Carrying case	0.8 kgs.	

* Specifications are subject to change without any notice

Standard Configuration

- Hexagonal wrench
- Adjusting pin
- Plumb bob
- Instruction manual
- Carrying case



TI Asahi Co., Ltd.
International Sales Department
 4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi
 Saitama, 339-0073 Japan
 Tel.: +81-48-793-0118
 Fax: +81-48-793-0128
 E-mail: International@tiasahi.com

www.tilinertec.com

Your Official Linertec Dealer



The CE marking assures that this product complies with the requirements of the EC directive for safety.